



Amario Grade 3 - Size 2



Cash Rating
£35,000



Jewellery Rating
£350,000



DIMENSIONS OF SAFE

All dims HxWxD

External dims: 500mm x 450mm x 450mm

Internal dims: 400mm x 350mm x 295mm

Usable depth when door is closed: 295mm

Handle on safe: 45mm extra onto dimensions.

Weight: 210kg

Volume (litres): 41

Safe is right hand hinged and opens to 180 degrees.

Door is removable when in the open position.

CHARACTERISTICS OF SAFE

If key locking the lock fitted will be a STUV 4.19.92 11 lever lock double bitting key retaining lock VDS class 2/EN 1300 class B fitted with 2 keys.

If electronic version is needed a Burton pulse dead bolt VDS KI-2 EN 1300 class B will be fitted

1 manager code (main code)

1 user code (secondary code)

RAL 7037 satin paint finish

Certified by ECBS to EN 1143-1 grade 3

AIS insurance approved, secured by design - police approved

The body has a cable hole predrilled top right-hand rear corner 10mm in diameter
QR code info sheet enclosed in safe.

LOCKING BOLTS

50mm thick door with 3-point locking bolts which are 25mm diameter. 2 on the top and 2 on the bottom 4 on the leading/opening edge of the door. Dog bolt/deadbolt on hinge side for protection even when hinges are cut or attacked.

FIXING BOLTS

Safe has 1 fixing hole in the base of the safe and 1 in the rear all are 25mm diameter and come c/w 1 fixing bolts 18mm in diameter and 150mm long. All fixing holes are covered by plastic caps. Rear fix hole is not drilled all the way through

SHELVES

Safe supplied with 2 shelves and multi position ladder racking. Shelf size 345mm x 290mm. Shelf positions on ladder racking are every 12mm apart

PLATES

Hardplate covering the lock area
Relockers are held with a ceramic plate
Second lock mounting position already on the door just needs drilling through the out skin of the

S1

S2